



### ZIP MESH

Tin-plated copper-mesh tape with Alu or Cu liner for highest efficiency. Ideal for short pieces or branches. Self-adhesive base assures firm positioning on the object, preventing slipping or overlapping. A reliable Faraday shield, solving many interference problems by reducing the effects of EMI.

Installation: 50% overlap, wrapping over cable, cable bundles, tubes, hoses etc., produces a very flexible 4-ply shielding. Like all EMI screening, grounding must be applied at both ends of the installations.

Rolls: 5 meters

**Material :** Cu / Sn-mesh with Alu or Cu-tape

**Construction :** NC

**Closing Systems :** [Tool for A track](#)

**Locking strength :** NC

**Color :** Silver or cooperly

**Breadth tape :** 25 and 75 mm

**Wall thickness mm :** 0.6 mm

**Shrink :** NC

**Diameter mm :** 1,5 up to 25,4 mm

**US/MIL- Standart :** NC

**UL Standart :** NC

**Shrink Temperature :** NC

**Temperature range :** - 30°C up to + 120°C

**Self-extinguishing :** YES

**UV/Ozone Resistant :** YES / YES

**Water Resistant :** YES

**Halogen/Cadmium Free :** NC

**Flame retardant :** NC

**Flammability :** NC

**Smoke :** NC

**Dielectric strength :** NC

**Abrasion :** NC

**Hardness: tubing/track :** NC

**Attenuation :** [Attenuation Table](#)

**Tools :** [tools](#)