



## ZT HIPOJACKET

Very high temperature and fire resistance. Can be use to protect any kind of cabling or for hydraulic and pneumatic pipe insulation. Hiprojacket offer high temperature protection and the outer cover offers excellent resistance to most industrial chemicals and hydraulic oils and are used in glass-, steel-, ceramics industry, steelworks, furnishing, machine- and apparatus-industry.

Temperature range : - 60° C up to + 1640° C ( max 30 S).

Rolls : 5 to 30 Mts depends on diameter.

**Material :** WOVEN FIBER-GLASS

**Coating :** IRONOXYDE SILICON RUBBER

**Construction :** NC

**Closing Systems :** NC

**Color :** Orange

**Wall thickness :** NC

**Base weight :** NC

**Finished coated weight :** NC

**Thread count / cm<sup>2</sup> :** NC

**Dimensions :** NC

**Diameter mm :** NC

**Inside diameter mm :** 6 up to 102 mm

**Water Resistant :** YES

**Flame Resistant :** NC

**Temperature range Mini  
maximum : continuous / short  
time :** NC

**Temperature range continuous  
maximum : 30 mn / 15 mn / 1  
mn :** - 60°C up to + 260°C + 800 C° / + 1100°C / + 1500°C

**Tools :** [tools](#)